

AutoLight Plus



WINDOW TINT TESTING

TEST ALL CLASSES OF VEHICLES

Why **AutoLight Plus**?

Window tinting can diminish driver vision through vehicle windows. This compromises the safety of the driver and their passengers.

Safety is jeopardised when approaching oncoming vehicles with dark window tinting. The internal space of the vehicle and its passenger's movements are not clearly visible.

What is **AutoLight Plus**?

AutoLight™ Plus is a portable Light Transmissibility Meter. The meter measures the amount of light transmitted through a tinted window to determine its compliance. It is a lightweight, accurate and easy to operate tool for law enforcement officers and compliance testers.

Some local regulations also require testing of tinted glass to ensure compliance with vehicle safety inspection requirements.

The AutoLight™ Plus meter provides inspectors with accurate readings that would otherwise be impossible by simple visual



How does **AutoLight Plus** work?

The light transmissibility meter consists of a light sensor built into the body of the instrument, a precision light source and an LED display.

By aligning the light source, and the sensor on either side of the window, the percentage of light transmitted through the window is measured.

The degree of visibility is obtained from the reading.

UPGRADE TO **AUTO**LIGHT MAGNETIC

THE AUTO**LIGHT**™MAGNETIC VERSION IS AN UPGRADE VERSION OF THE AUTO**LIGHT**. THE AUTO**LIGHT**™MAGNETIC HAS MAGNETS SO YOU CAN TEST HANDS FREE!



AutoLight Plus

WINDOW TINT TESTING

3 Easy testing steps with **AutoLight Plus**

STEP 1: Align AutoLight™ Plus to the side of the test window or windscreen so that the light source and light sensor overlap.

STEP 2: After aligning AutoLight™ Plus, press the measurement button to take a reading of the light transmitted through the window.

STEP 3: After the test is completed, the display window shows the percentage of light transmitted through the window.

FEATURES

- Easy to operate by aligning two reader tubes
- Simple one button operation
- Can be used for side windows or windscreens
- Calculates the percentage of light transmitted through windows
- Lightweight (350g)
- Compact (190mm x 60mm)
- Automatic start function
- Stores 20 test to memory
- Bluetooth connect to software, Workshop Pro10 and the Printer.
- Comes with self-checking calibrated Glass
- Should be calibrated annually

SPECIFICATIONS

SENSOR SPECIFICATION

- Spectral sensitivity conforming to photopic curve V (λ) of relative illuminous efficiency of the CIE 1931 standard observer for photopic vision
- Compliant with ISO 3538:1997

LIGHT SOURCE

- 2856°K \pm 50°K, conforming to CIE illuminant A
- Lamp voltage stabilised within $\pm 0.1\%$

ACCURACY

- Linear from 20 - 100%, $\pm 3\%$

DISPLAY

- LED readout 0 - 100%
- Resolution: 0.1%
- Display is optimised for Digital photography

POWER SOURCE

- 2 x MN 1604 batteries (9 volt)

